

# CITIZEN

**Designed and built for performance**  
Unique design in white or black, with outstanding features and reliability



### **Stylish, fast and compact**

The CL-E321's compact, modern, functional design takes up very little desk space, is easy to use and is also perfectly at home in any location, from warehouses to hospitals. It also has a fast print speed of 8 inches-per-second, is quick to setup and to load with media.

### **Well connected**

The CL-E321 features on-board LAN, USB and Serial interfaces. All industry-standard emulations are fully supported, with the option of remote operation via a web browser, using the Citizen LinkServer™ management tool.

### **Easy operation**

The CL-E321 is simple to use and intuitive, ensuring users waste no time when changing labels or adjusting settings.

## CL-E321

**Label, Desktop**

### **Applications**

- Courier
- Logistic / Transport
- Manufacturing
- Healthcare



The CL-E321 has a wide opening (180°) Hi-Lift™ case, and uses full size, 300m ribbons with standard 1 inch cores.

TOMORROW'S PRINTING TODAY



Ethernet LAN, USB and Serial interfaces as standard

### Specifications

|                              |                                                                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Model                        | CL-E321                                                                                                                                  |
| Printing Technology          | Thermal Transfer + Direct Thermal                                                                                                        |
| Resolution                   | 203 dpi                                                                                                                                  |
| Print Speed (maximum)        | 8 inches per second (200 mm/s)                                                                                                           |
| Print Width (maximum)        | 4 inches (104 mm)                                                                                                                        |
| Media Width (min to max)     | 1 - 4.6 inches (25 - 118 mm)                                                                                                             |
| Roll Size (max), Core Size   | Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)                                                                                |
| Media Thickness (min to max) | 63.5 to 190 µm                                                                                                                           |
| Media Length (min to max)    | 0.25 to 100 inches (6.35 to 2540 mm)                                                                                                     |
| Media Sensor                 | Fully adjustable gap and reflective black mark                                                                                           |
| Main Interface               | Triple interface USB 2.0, RS-232 and 10/100 Ethernet                                                                                     |
| Ribbon size                  | 2.6 inches (60 mm) maximum outside diameter. 300 metres length. 1 inch (25 mm core)                                                      |
| Ribbon winding & type        | Ink side out. Wax, Wax/Resin or Resin Type                                                                                               |
| Mechanism                    | Clamshell, easy-to-load, wide opening design                                                                                             |
| Control panel                | One LED, Control key: FEED                                                                                                               |
| Emulations (Languages)       | Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , CBI™ BASIC Interpreter, Eltron® EPL2® |
| Drivers and software         | Free-of-charge on CD with printer, including support for various platforms                                                               |
| Flash (Non-Volatile Memory)  | 16 MB total, 4MB available for user                                                                                                      |

## CL-E321

### Label, Desktop

### Features & Benefits

- Paper load: Hi-Lift™ mechanism and ClickClose™ closure
- Printing Speed: Ultra fast print out - up to 200mm per second (8 inches per second)
- Media support: Large media capacity - holds rolls up to 5 inches (127 mm)
- ENERGY STAR® compliant
- Small footprint



Media loading is simplified still further through the use of innovative ribbon holders, with a ClickClose™ closure mechanism ensuring complete reliability.

|                          |                        |
|--------------------------|------------------------|
| Model                    | CL-E321                |
| EMC and safety standards | CE, TUV, UL, FCC, VCCI |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0